


RIDUZIONE CONCENTRICA A SALDARE ASME BPE DT 4.1.3-1


codice	DN	DN1	C type A	C type B	F	F1
	inch	inch	mm	mm	mm	mm
5.641.S1.07-B	¾	½	101,6	54	19,05	12,7
5.641.S1.11-B	1	¾	101,6	54	25,4	19,05
5.641.S1.24-B	1 ½	1	127,0	63,5	38,1	25,4
5.641.S1.44-B	2	1 ½	133,4	63,5	50,8	38,1
5.641.S1.58-B	2 ½	2	139,7	63,5	63,5	50,8
5.641.S1.70-B	3	2 ½	139,7	66,7	76,1	63,5
5.641.S1.76-B	4	3	196,9	98,4	101,6	76,1

codice	DN	DN1	C type A	C type B	F	F1
	inch	inch	mm	mm	mm	mm
5.642.S1.24-B	1 ½	¾	127,0	76,2	38,1	19,01
5.642.S1.44-B	2	1	184,2	85,7	50,8	25,4
5.642.S1.58-B	2 ½	1 ½	184,2	85,7	63,5	38,1
5.642.S1.70-B	3	2	190,5	85,7	76,1	50,8
5.641.S1.76-B	4	2 ½	247,7	108	101,6	63,5