


ISO Welding support Lip


| codice | G | F | A | 2 S | 3 S | B |
|---------------|-------------|-----------|-----------|------------|------------|-----------|
| | inch | mm | mm | mm | mm | mm |
| 5.860.C9.13-A | 1 | 33,7 | 9 | 2 | 3 | 68 |
| 5.860.C9.29-A | 1 ¼ | 42,4 | 10 | 2 | 3 | 78 |
| 5.860.C9.38-A | 1 ½ | 48,3 | 10 | 2 | 3 | 88 |
| 5.860.C9.50-A | 2 | 60,3 | 12 | 2 | 3 | 102 |
| 5.860.C9.65-A | 2 ½ | 76,1 | 12 | 2 | 3 | 122 |
| 5.860.C9.71-A | 3 | 88,9 | 14 | 2 | 3 | 138 |
| 5.860.C9.75-A | 3 ½ | 101,6 | 14 | 2 | 3 | 148 |

| codice | G | F | A | 2 S | 3 S | B |
|---------------|-------------|-----------|-----------|------------|------------|-----------|
| | inch | mm | mm | mm | mm | mm |
| 5.860.C9.80-A | 4 | 114,3 | 14 | 2 | 3 | 158 |
| 5.860.C9.82-A | 5 | 139,7 | 16 | 2 | 3 | - |
| 5.860.C9.88-A | 6 | 168,3 | 16 | 2 | 3 | - |
| 5.860.C9.92-A | 8 | 219,1 | 16 | 2 | 3 | - |
| 5.860.C9.97-A | 10 | 273,0 | 18 | 2 | 3 | - |
| 5.860.C9.98-A | 12 | 323,9 | 20 | 2 | 3 | - |
| | | | | | | |