


**Coude 90° à dudgeonner polÄ¬ (pour tube DIN 11850)**


<b>codice</b>	<b>DN</b>	<b>F</b>	<b>S</b>	<b>R</b>	<b>B</b>	
	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>kg</b>
5.290.GG.06-A	15	18	1,5	35	47	0,05
5.290.GG.09-A	20	22	1,5	40	52	0,06
5.290.GG.12-A	25	28	1,5	50	70	0,11
5.290.GG.23-A	32	34	1,5	55	78	0,16
5.290.GG.32-A	40	40	1,5	60	85	0,21
5.290.GG.45-A	50	52	1,5	70	97	0,30
5.290.GG.57-A	60	60	1,5	75	110	0,42

<b>codice</b>	<b>DN</b>	<b>F</b>	<b>S</b>	<b>R</b>	<b>B</b>	
	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>kg</b>
5.290.GG.66-A	65	70	2	80	110	0,57
5.290.GG.72-A	80	85	2	90	123	0,78
5.290.GG.77-A	100	104	2	100	150	1,20