


Costruzione valvole e raccorderia in acciaio inox

**Ferrule à SOUDER CLAMP 3A (Ra < 0,5 µm)**



<b>codice</b>	<b>DN</b>	<b>L</b>	<b>F</b>	<b>C</b>	<b>S</b>	
	<b>inch</b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>kg</b>
4.540.LM.03-B	½	25,4	12,7	28,6	1,65	0,02
4.540.LM.07-B	¾	25,4	19,1	28,6	1,65	0,02
4.540.LM.11-B	1	50,4	25,4	28,6	1,65	0,08
4.540.LM.24-B	1 ½	50,4	38,1	28,6	1,65	0,07
4.540.LM.44-B	2	64	50,8	28,6	1,65	0,10
4.540.LM.58-B	2 ½	77,4	63,5	28,6	1,65	0,12
4.540.LM.70-B	3	90,9	76,1	28,6	1,65	0,15

<b>codice</b>	<b>DN</b>	<b>L</b>	<b>F</b>	<b>C</b>	<b>S</b>	
	<b>inch</b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>mm</b>	<b>kg</b>
4.540.LM.76-B	4	118,8	101,6	28,6	2,11	0,25
4.540.LM.86-B	6	167	154	28	2,77	0,40
4.540.LM.87-B	6	167	152,4	28	2,77	0,40
4.540.LM.90-B	8	217	204	28	2,77	50
4.540.LM.91-B	8	217	203,2	28	2,77	0,5
4.540.LM.96-B	10	268,5	254	28	3,40	*
4.540.LM.99-B	12	319,3	304,8	28	3,56	*